

BOOKLET

Tender design – blacksmith

AH51P-19S


Carina Pronsciaia, Jan 2020

VIA University College

8700 Horsens

Table of contents

- I. Basement floor plan for blacksmith, 1:100
- II. Groundfloor floor plan for blacksmith, 1:100
- III. Roof plan for blacksmith, 1:100
- IV. North and South elevations, 1:100
- V. East elevation, 1:100
- VI. West elevation, 1:100
- VII. Detail – hollow square column and foundation, 1:5
- VIII. Detail – IPE column and concrete wall, 1:5, updated
- IX. Detail – IPE column and beam, 1:2
- X. Detail – beam and façade, 1:5, updated
- XI. Detail – square column and beam, 1:2
- XII. Detail – balcony and façade, 1:5, updated
- XIII. Detail – balcony railing, 1:2
- XIV. Balcony plan – beams, 1:15
- XV. Balcony plan – decking, 1:15
- XVI. Balcony plan – aluminum sheets, 1:15
- XVII. Balcony front view, 1:15



LEGEND

- beam placed above the cut plane (overhead)
- existing beam
- new galvanized steel square hot rolled column
- new galvanized steel IPE column

BEAMS:

F1 - IPE100, S235, t = 5,7mm/4,1mm

Width: 55 mm

Length: 1600 mm

Relevant details:

K01_TXX_H5_E4_N11 - beam resting on internal wall

F2 - IPE80, S235, t = 5,2mm/3,8mm

Width: 46 mm

Length: 1060 mm

Relevant details:

K01_TXX_H5_E4_N11 - beam resting on internal wall

F3 - IPE120, S235, t = 6,3mm/4,4mm

Width: 64 mm

Length: 2950 mm

Relevant details:

K01_TXX_H5_E4_N13 - beam resting on external wall

F4 - IPE120, S235, t = 6,3mm/4,4mm

Width: 64 mm

Length: 2950 mm

Relevant details:
K01_TXX_H5_E4_N11 - beam resting on internal wall

F5 - HEB160, S235, t = 13mm/8mm

Length: 2950 mm
Relevant details:
K01_TXX_H5_E4_N12 - beam and IPE/HEB column

K01_TXX_H5_E4_N11 - beam resting on internal wall

F5.1 - HEB160, S235, t = 13mm/8mm

Length: 2950 mm
Relevant details:
K01_TXX_H5_E4_N12 - beam and IPE/HEB column

K01_TXX_H5_E4_N13 - beam resting on external wall

COLUMNS:

Col1, Col2 - 120 mm square hot rolled, S235, t = 10 mm

Length: 8370 mm

Relevant details:

K01_TXX_H5_E0_N05 - square column and foundation

K01_TXX_H5_E5_N02 - two square columns and deck

Col3, Col4, Col5, Col6 - IPE200, S235, t = 15mm/9mm

Length: 7517 mm

Relevant details:

K01_TXX_H5_E5_N01 - two IPE columns

K01_TXX_H5_E2_N09 - IPE column and concrete wall


Col7 - HEB160, S235, t = 13mm/8mm

Length: 2228 mm

Relevant details:

K01_TXX_H5_E0_N05 - square column and foundation

K01_TXX_H5_E4_N12 - beam and IPE/HEB column



Bring ideas to life
VIA University College

VIA Built Environment & Engineering
Campus VIA Horsens

PROJECT: Social housing refurbishment

DATE: 11/15/19


SUBJECT: Blacksmith - basement plan

SCALE: As indicated

DRAWN BY: Carina Pronscia (group 8)

CLASS: AH51P-19S

K01_TXX_H1_E1_N07

Cross section AA
K01_TXX_H3_EX_N03Cross section DD
K01_TXX_H3_EX_N06Cross section BB
K01_TXX_H3_EX_N04

LEGEND

new galvanized steel beam

new galvanized steel square hot rolled column

new galvanized steel IPE column

BEAMS:

E1 - HEB120, S235, t = 11mm/6,5mm

Length: 7280 mm

Relevant details:

K01_TXX_H5_E7_N12 - beam and square column

K01_TXX_H5_E4_N12 - beam and IPE column

E2 - HEB100, S235, t = 10mm/6mm

Length: 4817 mm

Relevant details:

K01_TXX_H5_E7_N12 - beam and square column

K01_TXX_H5_E4_N12 - beam and IPE column

E3 - HEB100, S235, t = 10mm/6mm

Length: 4390 mm

Relevant details:

K01_TXX_H5_E7_N12 - beam and square column

K01_TXX_H5_E4_N12 - beam and IPE column

E4 - HEB140, S235, t = 12mm/7mm

Length: 7720 mm

Relevant details:

K01_TXX_H5_E7_N12 - beam and square column

K01_TXX_H5_E4_N12 - beam and IPE column

COLUMNS:

C2 - IPE120, S235, t = 6,3mm/4,4mm

Width: 64 mm

Length: 4690 mm

Relevant details:

K01_TXX_H5_E4_N12 - beam and IPE column

Col1 - 120 mm square hot rolled, S235, t = 10 mm

Length: 8370 mm

Relevant details:

K01_TXX_H5_E5_N02 - two square columns and deck

Col2 - 120 mm square hot rolled, S235, t = 10 mm

Length: 8370 mm

Relevant details:

K01_TXX_H5_E5_N02 - two square columns and deck

Col3, Col4, Col5, Col6 - IPE200, S235, t = 15mm/9mm

Length: 7517 mm

Relevant details:

K01_TXX_H5_E5_N01 - two IPE columns





Bring ideas to life
VIA University College

VIA Built Environment & Engineering
Campus VIA Horsens

PROJECT: Social housing refurbishment	DATE: 11/15/19
SUBJECT: Blacksmith - roof plan	SCALE: As indicated
DRAWN BY: Carina Pronscia (group 8)	CLASS: AH51P-19S

K01_TXX_H1_E7_N05



LEGEND

new steel beam

new galvanized steel square hot rolled column

new galvanized steel IPE column

BEAMS:

C1 - IPE100, S235, length: 2050 mm, width: 55 mm

Relevant details:

K01_TXX_H5_E4_N13 - beam resting on external wall

D1 - UPE80, S235, length: 3050 mm

Relevant details:

K01_TXX_H5_E4_N09 - balcony railing

D2 - UPE80, S235, length: 2060 mm

Relevant details:

K01_TXX_H5_E4_N08 - balcony and facade

D3 - IPE100, S235, length: 2000 mm

Relevant details:

K01_TXX_H5_E4_N08 - balcony and facade

COLUMNS:

Col1, Col2 - 120 mm square hot rolled, S235, t = 10 mm

Length: 8370 mm

Relevant details:

K01_TXX_H5_E0_N05 - square column and foundation

K01_TXX_H5_E5_N02 - two square columns and deck

Col3, Col4, Col5, Col6 - IPE200, S235,

t = 15mm/9mm

Length: 7517 mm

Relevant details:

K01_TXX_H5_E5_N01 - two IPE columns

K01_TXX_H5_E2_N09 - IPE column and concrete wall



Bring ideas to life
VIA University College

VIA Built Environment & Engineering
Campus VIA Horsens

PROJECT: Social housing refurbishment

DATE: 11/15/19


SUBJECT: Blacksmith - north and south elevation

SCALE: As indicated

DRAWN BY: Carina Pronscia (group 8)

CLASS: AH51P-19S

K01_TXX_H2_EX_N08



LEGEND

[-----] new steel beam

[-----] new galvanized steel IPE column

BEAMS:

C2 - IPE120, S235, length: 4690 mm, width: 64 mm
Relevant details:

COLUMNS:


Col3, Col4, Col5, Col6 - IPE200, S235,
t = 15mm/9mm
Length: 7517 mm
Relevant details:
K01_TTX_H5_E5_N01 - two IPE columns
K01_TTX_H5_E2_N09 - IPE column
and concrete wall



Bring ideas to life
VIA University College

VIA Built Environment & Engineering
Campus VIA Horsens

PROJECT: Social housing refurbishment	DATE: 11/15/19	K01_TXX_H2_EX_N09
SUBJECT: Blacksmith - east elevation	SCALE: As indicated	
DRAWN BY: Carina Pronscia (group 8)	CLASS: AH51P-19S	




Bring ideas to life
VIA University College

VIA Built Environment & Engineering
Campus VIA Horsens

PROJECT: Social housing refurbishment	DATE: 11/15/19
SUBJECT: Blacksmith - west elevation	SCALE: As indicated
DRAWN BY: Carina Pronscia (group 8)	CLASS: AH51P-19S

K01_TXX_H2_EX_N10



Blacksmith - column and foundation

1 : 5

PROCESS:

PROCESS:

1. Casting 420 mm x 420 mm x 500 mm foundation footing (concrete and demolition trade)
2. 450 mm anchor rods inserted in freshly-casted foundation (concrete and demolition trade)
3. 320 mm x 320 mm x 15 mm steel base plate placed on top on levelling nuts in upper part of anchor rod
4. Base plate levelled with levelling nuts
5. Fixing upper washer and nut to fix base plate
6. Casting 15 mm of grouting under base plate
7. Delivering, lifting and welding 120x120mm hollow square column to base plate

DETAIL RELEVANT TO FOLLOWING COMPONENTS
Columns: Col1, Col2



Bring ideas to life
VIA University College


The image shows a detailed architectural floor plan of a building. The plan includes multiple levels, with the ground floor at the bottom and upper floors above. The building features a central atrium with a staircase. Various rooms are distributed across the levels, some with internal partitions. The exterior is shown with thick black lines for walls and windows, and a small entrance is indicated on the right side.

Cross section CC

VIA Built Environment & Engineering
Campus VIA Horsens

K01_TXX_H5_E0_N05


PROJECT: Social housing refurbishment	DATE: 11/15/19	K01_TXX_H5_E0_N05
SUBJECT: Blacksmith - detail - square column and foundation	SCALE: As indicated	
DRAWN BY: Carina Pronscia (group 8)	CLASS: AH51P-19S	



PROCESS:

1. Placing formwork and reinforcement (concrete and demolition trade)
2. Placing 300 mm deer anchor bolts (concrete and demolition trade)
3. Casting 400 mm wide basement wall (concrete and demolition trade)
4. 400 mm x 320 mm x 20 mm steel base plate placed on top on levelling nuts in upper part of anchor rod
5. Base plate levelled with levelling nuts
6. Fixing upper washer and nut to fix base plate
7. Casting 15 mm of grouting under base plate
7. Delivering, lifting and welding IPE200 column to base plate

DETAIL RELEVANT TO FOLLOWING COMPONENTS:
Columns: Col3, Col4, Col5, Col6



Cross section BB




Bring ideas to life
VIA University College

VIA Built Environment & Engineering
Campus VIA Horsens

PROJECT: Social housing refurbishment	DATE: 11/15/19
SUBJECT: Blacksmith - detail - IPE column and concrete wall	SCALE: As indicated
DRAWN BY: Junyu Jia/ Carina Pronscia (group 8)	CLASS: AH51P-19S

K01_TXX_H5_E2_N09




PROCESS:

1. Mounting of IPE200 steel column to concrete wall in the basement (Ref. K01_TXX_H5_E2_N09 - IPE column and concrete wall)
2. Delivering and lifting IPE100 steel beam with pre-casted end-plate
3. Connecting IPE100 beam to IPE200 beam with 8 pcs. 8 mm x 30 mm connector bolts


DETAIL RELEVANT TO FOLLOWING COMPONENTS:

- Col3, Col4, Col5, Col6
- C1, C2, E1, E2, E3, E4



Cross section BB

PROJECT: Social housing refurbishment	DATE: 11/15/19
SUBJECT: Blacksmith - Detail - IPE column and beam	SCALE: As indicated
DRAWN BY: Carina Pronscia (group 8)	CLASS: AH51P-19S




Steel beam to wall - plan view

1 : 5

Steel beam to wall - cross section

1 : 5



Cross section CC

PROCESS:

1. Demolition of an opening in external masonry wall (concrete and demolition trade)
2. Demolition of an internal wall and placing temporary supports
3. Placing prefabricated padstone on 12 mm mortar
4. Placing steel shims on top and fixing it with anchor bolts
5. Grouting of anchor bolts
6. Mounting HEB120 steel beam on top, fixing it to shims with 8 mm x 30 mm steel bolts and side welding

DETAIL RELEVANT TO FOLLOWING COMPONENTS:


Beams: A1-A12, B1-B3, C1, F1-F5.1



Bring ideas to life
VIA University College

VIA Built Environment & Engineering
Campus VIA Horsens

PROJECT: Social housing refurbishment	DATE: 01/06/20	K01_TXX_H5_E4_N13
SUBJECT: Blacksmith - detail - beam and facade	SCALE: As indicated	
DRAWN BY: Sarlota Sustrova/ Carina Pronscia (group 8)	CLASS: AH51P-19S	



PROCESS:

1. Mounting 120 mm hollow square column to foundation
2. Delivering and lifting HEB120 beam with pre-welded angle plates and web cleats
3. Connecting HEB120 beam to 120 mm hollow square column with 10 pcs. of 8 mm x 25 mm connection bolts


DETAIL RELEVANT TO FOLLOWING COMPONENTS:

- Columns: Col1, Col2
- Beams: E1, E2, E3, E4



Bring ideas to life
VIA University College


VIA Built Environment & Engineering
Campus VIA Horsens



Cross section BB

PROJECT: Social housing refurbishment	DATE: 15/11/19
SUBJECT: Blacksmith - detail - square column and beam	SCALE: As indicated
DRAWN BY: Carina Pronscia (group 8)	CLASS: AH51P-19S

K01_TXX_H5_E7_N12



PROCESS:

1. Demolition of existing bauma deck (demolition and concrete)
2. Demolition of the opening in the facade for balcony connector (demolition and concrete)
3. Placing SBC balcony connector with thermal separator, connecting reinforcement bars to existing reinforcement
4. Connecting IPE100 side beams to SBC connectors
5. Casting concrete on top of reinforcement connection (bricklayer)
6. Closing the opening in facade (bricklayer)

After closing the building and installing Stofix system:

7. Connecting UPE80 longitudinal beams to IPE100 beams
8. Connecting L-shaped beams to UPE80 beam
9. Connecting L-shaped longitudinal beam to IPE100 beams for drain layer
10. Connecting aluminum sheeting with 2% slope for the drain
11. Decking the balcony with timber boards
12. Siding the balcony with fibre cement boards
13. Fixing steel railings to the beams
14. Inserting glass panels

Fire demands: usage category 4, R60


1. D3 - IPE100 electro-galvanized steel beam fixed to SBC connector
Width: 55 mm
Thickness: 5,7 mm/4,1 mm
Length: 2000 mm
2. D1, D2 - UPE80 electro-galvanized steel beam
Width: 50 mm
Thickness: 7 mm
Length: 2800 mm
3. L-shaped electro-galvanized steel beam fixed to UPE80 neam with angle plates
Width: 40 mm
Height: 25 mm
Thickness: 4 mm
Spacing: 400 mm
4. 2 pcs. 40 mm x 40 mm x 2,5 mm angle plate
- pre-welded to L-beam
- connected to UPE beam with 2 pcs. 20 mm x 3 mm connection bolts
5. 20 mm x 3 mm electrogalvanized steel connection bolts
- 2 pcs. from two sides of L-beam
6. 25 mm x 100 mm x 2700 mm pressure-treated timber planks
- 5 mm between each row
- 4,2 mm x 45 mm timber-to-steel Simpson Quik screws
7. L-shaped electro-galvanized steel beam fixed to UPE80 neam with angle plates for aluminum sheet support and to create a slope
Width: 40 mm
Height: 25 mm
Thickness: 4 mm
Spacing: 400 mm
8. 2 mm x 600 mm x 1480 mm stainless heat-treated aluminum sheet
Fixed to UPE80 steel beam on the sides and welded together in the middle
Max. dimensions: 150 mm x 2500 mm x 8000 mm
9. 4 mm x 40 mm Z-profile stainless steel beam for siding support
Fixed to L-shaped beam underneath
Spacing: 400 mm
10. 6 mm x 1192 mm x 3050 mm fibre cement board fixed to Z-profile
11. Dyvel Drill HM 8 mm x 35 mm Cembril screw



Bring ideas to life
VIA University College

VIA Built Environment & Engineering
Campus VIA Horsens

PROJECT: Social housing refurbishment	DATE: 11/15/19	K01_TXX_H5_E4_N08
SUBJECT: Blacksmith - detail - balcony	SCALE: 1 : 5	
DRAWN BY: Carina Pronscia (group 8)	CLASS: AH51P-19S	



Balcony, railing - Blacksmith
1 : 2

PROCESS:

1. Demolition of existing bauma deck (demolition and concrete)
2. Demolition of the opening in the facade for balcony connector (demolition and concrete)
3. Placing SBC balcony connector with thermal separator, connecting reinforcement bars to existing reinforcement
4. Connecting IPE100 side beams to SBC connectors
5. Casting concrete on top of reinforcement connection (bricklayer)
6. Closing the opening in facade (bricklayer)
- After closing the building and installing Stofix system:
7. Connecting UPE80 longitudinal beams to IPE100 beams
8. Connecting L-shaped beams to UPE80 beam
9. Connecting L-shaped longitudinal beam to IPE100 beams for drain layer
10. Connecting aluminum sheeting with 2% slope for the drain
11. Decking the balcony with timber boards
12. Siding the balcony with fibre cement boards
13. Fixing steel railings to the beams
14. Inserting glass panels


Fire demands: usage category 4, R60

1. D3 - IPE100 electro-galvanized steel beam fixed to SBC connector
Width: 55 mm
Thickness: 5,7 mm/4,1 mm
Length: 2000 mm
2. D1, D2 - UPE80 electro-galvanized steel beam
Width: 50 mm
Thickness: 7 mm
Length: 2800 mm
3. L-shaped electro-galvanized steel beam fixed to UPE80 neam with angle plates, width: 40 mm, height: 25 mm, thickness: 4 mm, spacing: 400 mm
Connected with 4. 2 pcs. 40 mm x 40 mm x 2.5 mm angle plate
- pre-welded to L-beam
- connected to UPE beam with 2 pcs. 20 mm x 3 mm connection bolts through 20 mm x 3 mm electrogalvanized steel connection bolts
- 2 pcs. from two sides of L-beam
4. 25 mm x 100 mm x 2700 mm pressure-treated timber planks
- 5 mm between each row
- 4,2 mm x 45 mm timber-to-steel Simpson Quik screws
5. L-shaped electro-galvanized steel beam fixed to UPE80 neam with angle plates for aluminum sheet support and to create a slope
Width: 40 mm
Height: 25 mm
Thickness: 4 mm
Spacing: 400 mm
6. 2 mm x 600 mm x 1480 mm stainless heat-treated aluminum sheet
Fixed to UPE80 steel beam on the sides and welded together in the middle
Max. dimensions: 150 mm x 2500 mm x 8000 mm
7. 4 mm x 40 mm Z-profile stainless steel beam for siding support
Fixed to L-shaped beam underneath
Spacing: 400 mm
8. 6 mm x 1192 mm x 3050 mm fibre cement board fixed to Z-profile
9. Dyvel Drill HM 8 mm x 35 mm Cembrit screw
10. 35 mm x 1250 mm stainless steel railing and handrail
11. 2 x 45 mm angle brackets connecting each rail to UPE80 and longitudinal stiffener in IPE100 beam from two sides through 5 mm x 80 mm steel bolt
12. 10 mm x 600 mm x 950 mm clear glass panel

Bring ideas to life
VIA University College

VIA Built Environment & Engineering
Campus VIA Horsens

PROJECT:	Social housing refurbishment	DATE: 11/15/19	K01_TXX_H5_E4_N09
SUBJECT:	Blacksmith - detail - balcony railing	SCALE: 1 : 2	
DRAWN BY:	Carina Pronscia (group 8)	CLASS: AH51P-19S	




Bring ideas to life

VIA University College

VIA Built Environment & Engineering
Campus VIA Horsens

PROJECT: Social housing refurbishment	DATE: 11/15/19
SUBJECT: Balcony plan - beams	SCALE: 1 : 15
DRAWN BY: Carina Pronscia (group 8)	CLASS: AH51-19A

K01_TXX_H1_E4_N06




Balcony - decking

1 : 15

Bring ideas to life
VIA University College

VIA Built Environment & Engineering
Campus VIA Horsens

PROJECT: Social housing refurbishment	DATE: 11/15/19	
SUBJECT: Blacksmith - balcony with decking plan	SCALE: 1 : 15	K01_TXX_H1_E4_N07
DRAWN BY: Carina Pronscia (group 8)	CLASS: AH51P-19S	



PROCESS:

1. Demolition of existing bauma deck (demolition and concrete)
2. Demolition of the opening in the facade for balcony connector (demolition and concrete)
3. Placing SBC balcony connector with thermal separator, connecting reinforcement bars to existing reinforcement
4. Connecting IPE100 side beams to SBC connectors
5. Casting concrete on top of reinforcement connection (bricklayer)
6. Closing the opening in facade (bricklayer)

After closing the building and installing Stofix system:

7. Connecting UPE80 longitudinal beams to IPE100 beams
8. Connecting L-shaped beams to UPE80 beam
9. Connecting L-shaped longitudinal beam to IPE100 beams for drain layer
10. Connecting aluminum sheeting with 2% slope for the drain
11. Decking the balcony with timber boards
12. Siding the balcony with fibre cement boards
13. Fixing steel railings to the beams
14. Inserting glass panels


Balcony - aluminum sheeting
1 : 15

Bring ideas to life
VIA University College

VIA Built Environment & Engineering
Campus VIA Horsens

PROJECT: Social housing refurbishment	DATE: 11/15/19
SUBJECT: Blacksmith - balcony with sheeting plan	SCALE: 1 : 15
DRAWN BY: Carina Pronscia (group 8)	CLASS: AH51P-19S

K01_TXX_H1_E4_N08



West - blacksmith - balcony front view

1 : 15

PROCESS:

1. Demolition of existing bauma deck (demolition and concrete)
2. Demolition of the opening in the facade for balcony connector (demolition and concrete)
3. Placing SBC balcony connector with thermal separator, connecting reinforcement bars to existing reinforcement
4. Connecting IPE100 side beams to SBC connectors
5. Casting concrete on top of reinforcement connection (bricklayer)
6. Closing the opening in facade (bricklayer)

After closing the building and installing Stofix system:

7. Connecting UPE80 longitudinal beams to IPE100 beams
8. Connecting L-shaped beams to UPE80 beam
9. Connecting L-shaped longitudinal beam to IPE100 beams for drain layer
10. Connecting aluminum sheeting with 2% slope for the drain
11. Decking the balcony with timber boards
12. Siding the balcony with fibre cement boards
13. Fixing steel railings to the beams
14. Inserting glass panels

Fire demands: usage category 4, R60

Two demander design category 1, 100

1. D3 - IPE100 electro-galvanized steel beam fixed to SBC connector
Width: 55 mm
Thickness: 5,7 mm/4,1 mm
Length: 2000 mm
2. D1, D2 - UPE80 electro-galvanized steel beam
Width: 50 mm
Thickness: 7 mm
Length: 2800 mm
3. L-shaped electro-galvanized steel beam fixed to UPE80 neam with angle plates
Width: 40 mm
Height: 25 mm
Thickness: 4 mm
Spacing: 400 mm
4. 25 mm x 100 mm x 2700 mm pressure-treated timber planks
- 5 mm between each row
- 4,2 mm x 45 mm timber-to-steel Simpson Quik screws
5. L-shaped electro-galvanized steel beam fixed to UPE80 neam with angle plates for aluminum sheet support and to create a slope
Width: 40 mm
Height: 25 mm
Thickness: 4 mm
Spacing: 400 mm
6. 2 mm x 600 mm x 1480 mm stainless heat-treated aluminum sheet
Fixed to UPE80 steel beam on the sides and welded together in the middle
Max. dimensions: 150 mm x 2500 mm x 8000 mm
7. 4 mm x 40 mm Z-profile stainless steel beam for siding support
Fixed to L-shaped beam underneath
Spacing: 400 mm
8. 6 mm x 1192 mm x 3050 mm fibre cement board fixed to Z-profile
9. Dyvel Drill HM 8 mm x 35 mm Cembrit screw
10. 35 mm x 1250 mm stainless steel railing and handrail
11. 2 x 45 mm angle brackets connecting each rail to UPE80 and longitudinal stiffener in IPE100 beam from two sides through 5 mm x 80 mm steel bolt
12. 10 mm x 600 mm x 950 mm clear glass panel



Bring ideas to life
VIA University College

VIA Built Environment & Engineering
Campus VIA Horsens

PROJECT: Social housing refurbishment	DATE: 11/15/19	K01_TXX_H2_EX_N11
SUBJECT: Blacksmith - balcony front view	SCALE: 1 : 15	
DRAWN BY: Carina Pronscia (group 8)	CLASS: AH51P-19S	